

**Listing of the Claims**

This Listing of the Claims replaces all previous listings of the claims in this application.

1. (Canceled)
2. (Currently amended) The fuel cell according to claim [[+]] 62, wherein the hydrocarbon is a petroleum distillate.
3. (Previously presented) The fuel cell according to claim 2, wherein the petroleum distillate is selected from the group consisting of gasoline, diesel oil, naphtha, JP-4, JP-5, JP-8, kerosene, motor oil, natural gas, fuel oil, and mixtures thereof.
4. (Previously presented) The fuel cell according to claim 3, wherein the petroleum distillate is selected from the group consisting of JP-4, JP-5, JP-8, and mixtures thereof.
5. (Previously presented) The fuel cell according to claim 3, wherein the petroleum distillate is selected from the group consisting of naphtha, kerosene, fuel oil, and mixtures thereof.
6. (Previously presented) The fuel cell according to claim 3, wherein the petroleum distillate is selected from the group consisting of gasoline, diesel oil, natural gas, and mixtures thereof.
7. (Original) The fuel cell according to claim 2, wherein the hydrocarbon comprises an alcohol.
8. (Previously presented) The fuel cell according to claim 7, wherein the alcohol is selected from the group consisting of methanol, ethanol, and mixtures thereof.
9. (Previously presented) The fuel cell according to claim 2, wherein the hydrocarbon is selected from the group consisting of dry methane, butane, toluene, decane, and mixtures thereof.
10. (Currently amended) The fuel cell according to claim [[+]] 62, wherein the sulfur-containing hydrocarbon fuel has a sulfur content of from about 1 ppm to about 1000 ppm.

11. (Original) The fuel cell according to claim 10, wherein the sulfur-containing hydrocarbon fuel has a sulfur content of from about 10 ppm to about 1000 ppm.
12. (Original) The fuel cell according to claim 11, wherein the sulfur-containing hydrocarbon fuel has a sulfur content of from about 20 ppm to about 1000 ppm.
13. (Original) The fuel cell according to claim 12, wherein the sulfur-containing hydrocarbon fuel has a sulfur content of from about 100 ppm to about 1000 ppm.
14. (Original) The fuel cell according to claim 13, wherein the sulfur-containing hydrocarbon fuel has a sulfur content of from about 250 ppm to about 1000 ppm.
15. (Currently amended) The fuel cell according to claim ~~[[+]]~~ 62, wherein the solid electrolyte is an oxide ion conducting material.
16. (Previously presented) The fuel cell according to claim 15, wherein the oxide ion conducting material is selected from the group consisting of doped ceria, doped zirconia, and doped lanthanum gallate.
17. (Previously presented) The fuel cell according to claim 16, wherein the doped ceria is selected from the group consisting of gadolinium doped ceria, samarium-doped ceria, yttria-doped ceria, and mixtures thereof.
18. (Previously presented) The fuel cell according to claim 15, wherein the oxide ion conducting material is yttria-doped zirconia.
19. (Previously presented) The fuel cell according to claim 16, wherein the doped zirconia is scandium-doped zirconia.
20. (Canceled)
21. (Currently amended) The process according to claim ~~[[29]]~~ 63, wherein the hydrocarbon is a petroleum distillate.

22. (Previously presented) The process according to claim 21, wherein the petroleum distillate is selected from the group consisting of gasoline, diesel oil, naphtha, JP-4, JP-5, JP-8, kerosene, motor oil, natural gas, fuel oil, and mixtures thereof.
23. (Previously presented) The process according to claim 22, wherein the petroleum distillate is selected from the group consisting of JP-4, JP-5, JP-8, and mixtures thereof.
24. (Previously presented) The process according to claim 22, wherein the petroleum distillate is selected from the group consisting of naphtha, kerosene, fuel oil, and mixtures thereof.
25. (Original) The process according to claim 22, wherein the petroleum distillate comprises gasoline.
26. (Original) The process according to claim 22, wherein the petroleum distillate comprises diesel oil.
27. (Currently amended) The process according to claim ~~[[20]]~~ 63, wherein the hydrocarbon is selected from the group consisting of alcohols, dry methanes, butane, toluene, decane, and mixtures thereof.
28. (Original) The process according to claim 27, wherein the hydrocarbon comprises an alcohol.
29. (Previously presented) The process according to claim 28, wherein the alcohol is selected from the group consisting of methanol, ethanol, and mixtures thereof.
30. (Currently amended) The process according to claim ~~[[20]]~~ 63, wherein the sulfur-containing hydrocarbon has a sulfur content of from about 10 ppm to about 1000 ppm.
- 31.-53. (Canceled without prejudice)
54. (Canceled)
55. (Currently amended) The fuel cell of claim ~~[[+]]~~ 62, wherein the anode further comprises copper deposited in the pores.

56. (Currently amended) The process of claim ~~[[20]]~~ 63, wherein the anode further comprises copper deposited in the pores.
57. (Canceled)
58. (Currently Amended) The fuel cell of claim ~~[[57]]~~ 65, wherein the anode further ~~comprising~~ comprises copper ~~impregnated~~ deposited in the pores.
59. (Canceled)
60. (Currently Amended) The process of claim ~~[[59]]~~ 66, wherein the anode further comprises copper ~~impregnated~~ deposited in the pores.
61. (Canceled)
62. (New) A solid oxide fuel cell that directly operates with a sulfur-containing hydrocarbon fuel that does not have to undergo prior treatment to remove organic sulfur compounds comprising:
- (a) a solid electrolyte comprising an electronic insulator which allows transfer of anions;
  - (b) an essentially nickel-free porous anode containing at least ceria deposited in the pores;
  - (c) a cathode;
  - (d) a fuel comprising a sulfur-containing hydrocarbon having a sulfur content of from about 1 ppm to about 5000 ppm; and
  - (e) an oxygen source;

wherein at least the solid electrolyte and porous anode form a porous anode layer and a dense solid electrolyte layer, wherein like particles of the porous anode and the solid electrolyte are bonded together, the porous anode layer further deposited with at least ceria to form a porous anode with at least ceria deposited in the pores.

63. (New) A process of producing electrical energy, comprising:
- (a) providing a solid oxide fuel cell that directly operates with a sulfur-containing hydrocarbon fuel that does not have to undergo prior treatment to remove organic sulfur compounds, the solid oxide fuel cell comprising: a solid oxide electrolyte that is an electronic insulator which allows transfer of anions; an essentially nickel-free porous anode containing at least ceria deposited in the pores; and a cathode, wherein at least the solid oxide electrolyte and porous anode form a porous anode layer and a dense solid electrolyte layer, wherein like particles of the porous anode and the solid electrolyte are bonded together prior to depositing at least ceria into the pores of the anode to form a porous anode with at least ceria deposited in the pores;
  - (b) contacting said cathode with an oxygen source; and
  - (c) contacting said porous anode with a fuel comprising a sulfur-containing hydrocarbon having a sulfur content of from about 1 ppm to about 5000 ppm.
64. (New) A solid oxide fuel cell that directly operates with a sulfur-containing hydrocarbon fuel that does not have to undergo prior treatment to remove organic sulfur compounds comprising:
- (a) a solid electrolyte comprising an electronic insulator which allows transfer of anions;
  - (b) an essentially nickel-free porous ceramic-metal composite anode containing at least copper deposited in the pores;
  - (c) a cathode;
  - (d) a fuel comprising a sulfur-containing hydrocarbon having a sulfur content of from about 1 ppm to about 5000 ppm; and
  - (e) an oxygen source;

wherein at least the solid electrolyte and porous anode form a porous anode layer and a dense solid electrolyte layer wherein like particles of the porous anode and the solid electrolyte are bonded together, the porous anode layer further deposited with a salt of at least copper to form a porous anode with at least copper deposited in the pores.

65. (New) A solid oxide fuel cell that directly operates with a sulfur-containing hydrocarbon fuel comprising:

- (a) a solid electrolyte comprised of an electronic insulator which allows transfer of anions; an essentially nickel-free porous anode containing at least ceria deposited in the pores; and a cathode;
- (b) a fuel comprising a sulfur-containing hydrocarbon having a sulfur content of from about 1 ppm to about 5000 ppm; and
- (c) an oxygen source;

wherein like particles of the porous anode and the solid electrolyte are bonded together.

66. (New) A process of producing electrical energy, comprising:

- (a) providing a solid oxide fuel cell that directly operates with a sulfur-containing hydrocarbon fuel, the solid oxide fuel cell comprising a solid oxide electrolyte that is an electronic insulator which allows transfer of anions; an essentially nickel-free porous anode containing at least ceria deposited in the pores; and a cathode;
- (b) contacting said cathode with an oxygen source; and
- (c) contacting said porous anode with a fuel comprising a sulfur-containing hydrocarbon having a sulfur content of from about 1 ppm to about 5000 ppm;

wherein like particles of the porous anode and the solid electrolyte are bonded together.

67. (New) A solid oxide fuel cell that directly operates with a sulfur-containing hydrocarbon fuel comprising:

- (a) a solid electrolyte comprising an electronic insulator which allows transfer of anions; an essentially nickel-free porous ceramic-metal composite anode containing at least copper deposited in the pores; and a cathode;
- (b) a fuel comprising a sulfur-containing hydrocarbon having a sulfur content of from about 1 ppm to about 5000 ppm; and
- (c) an oxygen source;

wherein like particles of the porous anode and the solid electrolyte are bonded together.